



Material Safety Data Sheet (MSDS)

Wood Veneer Product

Important Notice: This Material Safety Data Sheet (MSDS) is written by PT. KUTAI TIMBER INDONESIA in accordance with Worksafe Australia and OSH New Zealand guidelines. As such, the information contained herein must not be altered, deleted or added to. PT. KUTAI TIMBER INDONESIA will issue a new MSDS when there is a change in product specifications and/or guidelines or regulations. PT. KUTAI TIMBER INDONESIA will not accept responsibility for any changes made to its MSDS in content by any other persons.

IDENTIFICATION:

Product Names	: Interior Plywood equivalent to AS/NZS 2270 : Exterior Plywood equivalent to AS/NZS 2271
UN Number	: None allocated
Registered Trade Name	: PT. Kutai Timber Indonesia
Dangerous Goods Class	: None allocated
Hazchem Code	: None allocated
Poisons Schedule	: None allocated
Use	: Residential, commercial, and industrial, furniture and/or general purpose building material

PHYSICAL DESCRIPTION / PROPERTIES

Appearance	: The products are manufactured as pressed boards ranging in thickness from 2.4 mm to 32.0 mm. They are constructed from Tropical Forest Hardwoods and Fast Growing Species, which are bonded together with resin.
Odour	: No distinctive odour. Newly manufactured plywood and freshly machined surfaces tend to have the odour of the wood species from which the plywood is manufactured.
Boiling Point	: Not applicable
Vapour Pressure	: Not applicable
Vapour Density	: Not applicable
Melting Point	: Not applicable
Solubility in Water	: Highly insoluble
Flashpoint	: Not applicable
Specific Gravity	: 0.30 – 1.00
Flammability in air	: Fine airborne wood dust, generated during machining of the product, can spontaneously ignite.
Auto Ignition Temperature	: >200°C

INGREDIENTS

<u>Substance/Chemical Entity</u>	<u>CAS No.</u>	<u>Proportion by weight</u>
Wood Veneer	None	>92%
Urea formaldehyde resin	9011-05-6	<8%
or		
Melamine urea formaldehyde resin	25036-13-9	<8%
Melamin formaldehyde resin	9003-08-1	<8%
or		
Phenol formaldehyde resin	9003-35-4	<8%
Insecticide, as		
Bifenthrin	82657-04-3	<0.015%
or		
(±)-α-Cyano-3-phenoxybenzyl		
(+)-cis/trans-chrysanthemate		
(Cyphenothrin)	39515-40-7	<0.015%

Note: The wood veneer, the resins and the insecticide are bonded together under heat and pressure. The process cures the resin, however small amounts of formaldehyde may be released from the finished product. In newly manufactured plywood, formaldehyde emission has been measured in the range 0.03 – 0.5 mg/L using the small scale chamber test method.

HEALTH HAZARD INFORMATION

Health Effects : Plywood is not classified as hazardous, however handling panel edges and surfaces may cause splinters.

Known healthy effects are:

Cured Resin : The cured resin is inert and not likely to contribute to health effects

Formaldehyde : Formaldehyde is a naturally occurring gas that is irritating to the nose, throat, eyes and skin at high concentrations. It is recommended that storage areas be well ventilated to avoid any irritations due to a buildup of formaldehyde.

The International Agency for Research on Cancer (IARC), a division of the World Health Organization has reclassified formaldehyde from a group 2A suspected carcinogen to a known carcinogen. (Cancer causing properties of formaldehyde are only evident at very high concentrations, hundreds of times greater than levels emitted from plywood products)

Sealing the plywood with paint, varnish or other surface finishes further reduces any emissions.

As veneer products have emission levels of 0.03 to 1.0 mg/L (Japanese Agriculture standards/JAS) and well below WHO recommendations of 0.1mg/L, it is unlikely that the presence of traces of formaldehyde on the product poses a health risk.

Wood dust : When the boards are machined (sawn, sanded, drilled, planed etc) wood dust is produced. Wood dust and splinters may cause irritation to the nose, throat, eyes and skin. The wood dusts may also be a sensitizer and some people may develop allergic dermatitis or asthma. Inhalation of wood dust may

increase the risk of nasal and Para nasal sinus cancers. Exposure to the wood dust produced through machining may result in the following health effects:

Acute:

- Ingestion** : Unlikely to occur, however swallowing wood dust may result in abdominal discomfort
- Eyes** : The wood dust may be irritating to the eyes causing discomfort and redness
- Skin** : The wood dust may be irritating to the skin, resulting in itching and on occasions, a red rash. Allergic contact dermatitis may occur.
- Inhaled** : The wood dust may irritate the throat and lungs especially in people with upper respiratory tract or chest complaints. Asthma may occur.
- Chronic** : Repeated exposures to uncontrolled wood dust from these boards over many years may increase the risk of allergies, dermatitis, asthma or chronic nose or throat irritation in some people, the risk of nasal or Para nasal sinus cancers may also be increased. If the workplace practices noted in this MSDS are followed, no chronic health effects are anticipated.

First Aid:

- Swallowed** : Rinse mouth with water and give water to drink. If abdominal discomfort occurs, seek medical advice.
- Eye** : Flush with flowing water for at least 15 minutes and if symptoms persist, seek immediate medical attention. Contact lenses to be removed.
- Skin** : Wash with mild soap and running water
- Inhaled** : Move from dust affected area to fresh air.
- Advice to Doctor** : Treat symptomatically

PRECAUTIONS FOR USE

Exposure Standards:

DESCRIPTION	OSH New Zealand	Worksafe Australia
Wood Dust	5mg/m ³ time weighted average (TWA)	5mg/m ³ time weighted average (TWA) 10mg/m ³ short term exposure limit (STEL)
Formaldehyde	1.0ppm(1.2mg/m ³) time weighted average (TWA) 2.0ppm (2.5mg/m ³) short term exposure limit (STEL)	1.0ppm(1.2mg/m ³) time weighted average (TWA) 2.0ppm (2.5mg/m ³) short term exposure limit (STEL)

Wood dust is also listed as a sensitizer and the Exposure standard is under review. In the interests of maintaining a safe working environment, it is recommended that workplace exposures to wood dust should not exceed 1.0mg/m³ time weighted average (TWA).

- Engineering Controls** : All work with these boards should be carried out in such a way as to minimize the generation of wood dust. Under factory conditions, machining should be done with equipment fitted with exhaust devices capable of

removing wood dust at the source. Hand power tools should be fitted with dust bags. Work areas should be well ventilated. They should be cleaned at least daily, and wood dust should be removed by vacuum cleaning or by wet sweeping.

- Skin Protection** : Wear loose, comfortable clothing. Long sleeved shirts, trousers and comfortable work gloves (AS 2161) should be worn if skin irritation occurs and to minimize risk of splinters. After handling boards, wash with a mild soap and water. Do not scratch or rub the skin if it becomes irritated. Wash work clothes regularly and if possible separate from other clothes.
- Respiratory Protection** : If wood dust exposures are not controlled when machining (sawing, routing, planing, drilling, sanding, etc) a class P1 or P2 replaceable filter or disposable face piece respirator should be worn. Respirators should comply with AS/NZS 1716, and be selected, used and maintained in accordance with AS/NZS 1715.
- Eye Protection** : Safety glasses or non-fogging goggles (AS/NZS 1337) should be worn when machining.
- Flammability** : These boards are flammable but difficult to ignite. Avoid a buildup of wood dust and keep all storage and work areas well ventilated. Avoid sources of radiant heat and flame and avoid sparks and sources of ignition in all electrical equipment, including dust extraction equipment. People must not smoke in storage or work areas.

SAFE HANDLING INFORMATION

- Storage and transport** : Boards should be stored in well ventilated areas away from sources of heat, flames or sparks. No special transport requirements are considered necessary
- Spills and Disposals** : Off-cuts and general waste material should be placed in containers and disposed of at approved landfill sites, or burnt in an approved furnace or incinerator, in accordance with disposal authority guidelines. Wood dust should be cleaned up by vacuuming or wet sweeping.
- Fire / Explosion Hazard** : Early fire hazard properties are determined in accordance with AS 1530 Part3
- Ignitability Index** : 14
- Spread of Flame Index** : 7-8
- Heat Evolved Index** : 8-10
- Smoke Developed Index** : 2-3
- Burning or smoldering boards or wood dust can generate carbon dioxide and other pyrolysis products typical of burning organic material. Dry wood dust in high concentrations can be explosive. Use water or dry chemical fire extinguishers.
- Smoking** : Storage and work areas should be smoke free.

CONTACT POINT

PT. KUTAI TIMBER INDONESIA
Jl. Tanjung Tembaga Baru/Pelabuhan
Probolinggo, East Java
Phone: + 62 0335 422412
Fax: + 62 0335 421669
Post Code: 67201

“The information contained in this document is based on data available at the time of writing, which we believe is accurate and reliable. From time to time, information will be changed and added to as new data becomes available. No responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purpose and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of the information.”

H. Suda
Deputy GM